

# Platinum Series® Aluminium Cladding

Louvreclad Platinum Series® is our aluminium rain screen cladding. Custom engineered, it offers bespoke designs with concealed fixing systems. Ideal solution for long-lasting, low-maintenance facades in powder coat or anodised finishes.

## Features

### PERFORMANCE

#### Durable and Resilient

Custom-engineered from 3mm-8mm aluminium plates, the Platinum Series® offers a robust, non-combustible, and corrosion-resistant cladding solution, ensuring long-lasting performance in any environment.

### AESTHETICS

#### Bespoke Design

Tailored to each project, this rain-screen cladding system can be custom cut, folded, and engineered to suit any design intent. Available in powder-coated or anodised finishes for a sleek, modern look.

### DESIGN

#### Versatile and Integrated

Compatible with Polaris and Ascot Series®, the Platinum Series® offers bespoke sub-framing and concealed fixing systems, providing seamless integration with other architectural elements.

Specifications

AUSTRALIAN STANDARDS  
AS1170

MATERIAL  
Aluminium available in various  
grades to suit the finish

FINISH  
Interpon powder coated range,  
Dulux powder coated range,  
Timber Grain Powdercoat range,  
Sapphire anodised range,  
Universal anodised range, AAF  
anodised range

INSTALLATION  
Installation and mounting  
details will be designed in  
accordance with proprietary  
systems and recommendations  
as designed and manufactured  
by Louvreclad.



## Explore the profile options

---

### Platinum Series®

Premium custom folded and fabricated solid aluminium rain screen cladding solution



## Technical Data Disclaimer

- Indicative maximum span provided are based on generic permissible design wind pressure of 2kPa.
- Span values and product technical information provided are subjected to variance by project specific requirements & influence factors such building location, terrain category & local pressure effects.
- Span values provided are based on typical scenario where product specified are fixed at one end; simply supported at the other end and in either horizontal or vertical orientation.
- If the product specified is required to function as barrier for fall protection or as trafficable element, maximum span and pitch nominated may be reduced.
- Spans values provided could be influenced and reduced when used in dynamically sensitive wind environment.
- For project specific product selection or preliminary design & engineering consultation, please contact 1300 165 678 or [sales@louvrecad.com](mailto:sales@louvrecad.com) to arrange or book a meeting.







## Inspire with Quality

As leaders in the building envelope market, we are known for exceptional quality and lasting value. Our credibility, wealth of knowledge, and unmatched competence enable us to inspire exterior solutions that look good and perform better.



## The MadeRight Guarantee

Following our proven process enables us to develop solutions we're proud to put our mark of quality to. We guarantee that all projects will be delivered in a timely manner, be on specification, engineered to Australian standards and finished to the highest quality.



## Made to Perform

Louvreclad solutions are made to last and manufactured on-site using high-quality Australian aluminium and steel. As an organisation we are driven to get a thousand things right everyday to achieve our vision to be the face of Australian Building. Our facades are not here to be average, they are here to perform – and so are we.

# Speak to an expert

Reach out today to discuss your facade solution requirements; we would love to hear from you.



Made to Perform

1300 165 678

[sales@louvrecld.com](mailto:sales@louvrecld.com)

[louvrecld.com](http://louvrecld.com)